MP900 Non-Inductive Power Film Resistors

Product overview

A resistance film is fired onto a flat ceramic substrate. The element and terminal attachment areas are encapsulated, while the ceramic rear face remains exposed and flush with the mounting surface for heat transfer.



Features

- Non-inductive geometry for fast switching, snubbers and RF applications.
- Resistive element electrically isolated from the mounting surface.
- Power capability depends on case temperature; design cooling with the derating curve.
- Standard resistance and tolerance choices; custom requirements by agreement.

Electrical specifications

Parameter	MP915	MP916	MP925	MP930
Package	TO-126	TO-220	TO-220	TO-220
Resistance range	0.020 Ω–1 kΩ	0.010–0.019 Ω	5.00–100 kΩ	0.020 Ω–4.99 kΩ
Power at Tc =25°C	15 W	16 W	25 W	30 W
Maximum operating voltage	200 V	Power limited	500 V	250 V
Thermal resistance RθJC	8.33 °C/W	7.81 °C/W	5.00 °C/W	4.17 °C/W
Maximum temperature Tmax	150°C	150°C	150°C	150°C
Free-air power at 25°C	1.25 W	2.25 W	2.25 W	2.25 W
Operating temperature	-55°C to model-specific Tmax			
Dielectric withstand	1500 Vrms AC			
Insulation resistance	≥10,000 MΩ			
Typical series inductance	10 nH			
Terminal material	Solderable			


Power and overload capability are derated by case temperature. “Power limited” means voltage must be determined from resistance and allowable power.

MP900 Non-Inductive Power Film Resistors


Dimensions and construction

Dimensions follow the source: inches with millimeters in parentheses. Structures, holes and terminal shapes follow the original drawing.

MP915 • TO-126



MP916 / MP925 / MP930 • TO-220



MP900 Non-Inductive Power Film Resistors

Temperature coefficient

Resistance interval	TCR / ppm/°C
R ≥0.50 Ω	-20...+80
0.050–0.49 Ω	0...+200
0.020–0.049 Ω	0...+300
0.010–0.019 Ω	0...+500


TCR is referenced to 25°C, with ΔR measured at Tmax.

Performance and tests

Test	Conditions	Resistance change limit
Load stability	2000 h at rated power; derated by case temperature	±(1.0%R + 0.0005 Ω)
Momentary overload	5 s; voltage ≤1.5× maximum continuous operating voltage	±(0.5%R + 0.0005 Ω)
Moisture resistance	MIL-STD-202, Method 106	±(0.5%R + 0.0005 Ω)
Thermal shock	MIL-STD-202, Method 107, Condition F	±(0.5%R + 0.0005 Ω)
Mechanical shock	100 G; MIL-STD-202, Method 213, Condition I	±(0.4%R + 0.0005 Ω)
High-frequency vibration	MIL-STD-202, Method 204, Condition D	±(0.4%R + 0.0005 Ω)
Terminal strength	MIL-STD-202, Method 211, Condition A; 5 lb pull	±(0.2%R + 0.0005 Ω)

R is nominal resistance. Momentary overload: 2× rated power for MP820, MP821 and MP850; 1.5× for MP825 and the MP900/MP9100 models.

Power derating curve



100% at Tc =25°C; linear derating to zero at Tmax.

MP900 Non-Inductive Power Film Resistors

Standard resistance values and tolerance

MP915

0.020 Ω 5%	0.025 Ω 5%	0.030 Ω 5%	0.033 Ω 5%	0.040 Ω 5%	0.050 Ω	0.075 Ω	0.10 Ω
0.15 Ω	0.20 Ω	0.25 Ω	0.30 Ω	0.33 Ω	0.40 Ω	0.50 Ω	0.75 Ω
1.00 Ω	1.50 Ω	2.00 Ω	2.50 Ω	3.00 Ω	3.30 Ω	4.00 Ω	5.00 Ω
7.50 Ω	8.00 Ω	10.0 Ω	12.0 Ω	15.0 Ω	20.0 Ω	25.0 Ω	27.0 Ω
30.0 Ω	33.0 Ω	40.0 Ω	47.0 Ω	50.0 Ω	56.0 Ω	75.0 Ω	100 Ω
120 Ω	150 Ω	200 Ω	250 Ω	300 Ω	330 Ω	400 Ω	470 Ω
500 Ω	560 Ω	750 Ω	1.00 kΩ				

Standard ±1%, except low-resistance entries marked 5%; ±5% and ±20% available for most values.

MP916

0.010 Ω 5%	0.015 Ω 5%						

Standard ±5%; ±20% available.

MP925

5.00 kΩ	7.50 kΩ	10.0 kΩ	15.0 kΩ	20.0 kΩ	25.0 kΩ	30.0 kΩ	33.0 kΩ
40.0 kΩ	47.0 kΩ	50.0 kΩ	56.0 kΩ	68.0 kΩ	75.0 kΩ	82.0 kΩ	100 kΩ

Standard ±1%, except low-resistance entries marked 5%; ±5% and ±20% available for most values.

MP930

0.020 Ω 5%	0.025 Ω 5%	0.030 Ω 5%	0.033 Ω 5%	0.040 Ω 5%	0.050 Ω	0.075 Ω	0.10 Ω
0.15 Ω	0.20 Ω	0.25 Ω	0.30 Ω	0.33 Ω	0.40 Ω	0.50 Ω	0.75 Ω
1.00 Ω	1.50 Ω	2.00 Ω	2.50 Ω	3.00 Ω	3.30 Ω	4.00 Ω	5.00 Ω
7.50 Ω	8.00 Ω	10.0 Ω	12.0 Ω	15.0 Ω	20.0 Ω	25.0 Ω	27.0 Ω
30.0 Ω	33.0 Ω	40.0 Ω	47.0 Ω	50.0 Ω	56.0 Ω	75.0 Ω	100 Ω
120 Ω	150 Ω	200 Ω	250 Ω	300 Ω	330 Ω	400 Ω	470 Ω
500 Ω	560 Ω	750 Ω	1.00 kΩ	1.50 kΩ	2.00 kΩ	2.50 kΩ	3.00 kΩ
3.30 kΩ	4.00 kΩ						

Standard ±1%, except low-resistance entries marked 5%; ±5% and ±20% available for most values.

Mounting and selection

• Use a smooth, flat, clean heatsink and a thermal interface such as grease. The entire exposed heat-dissipating rear surface must contact the heatsink.

• For screw mounting, use a compression washer providing 150–300 lb (665–1330 N). The mounting torque limit to avoid package damage is 8 in·lbf (0.90 N·m).

• A spring clip should apply 8–30 lb (35–130 N) at the package center. Use a rounded or smooth contact area to avoid point loading. A pressure bar with a larger contact area is another option.

• Across the full application temperature range, satisfy Tc + RθJC × P ≤ Tmax. Measure case temperature at the mounting-surface center with the part properly mounted and electrically loaded.

• Measure resistance and inductance 0.2 in (5.08 mm) from the resistor body. For dielectric tests, short the terminals and test against the mounting metal surface or a metal clip contacting the package top.

Ordering example: MP915 - 50.0 - 1% (model - resistance - tolerance). Packaging: 50 pieces per tube. Custom resistance and tolerance by agreement.

Standard values are selected from the source series list within each model’ s rated range. MP915, MP916, MP925 and MP930 have a 50-piece minimum, ordered in full-tube increments.